

# G101Q9-A

10.1" Qualcomm® 6490 Rugged Robotic Controller



CE

FC

## KEY FEATURES

- 10.1" 1920 x 1200 IPS LED Panel with direct optical bonding
- Qualcomm® 6490 (Octa-core 2.7 GHz) processor
- All-weather, dust, and water-resistant design (IP65). MIL-grade drop, Shock and vibration
- Supports WIFI, BT and optional 4G/5G
- With one removable battery

## INTRODUCTION

The 10.1" Qualcomm® 6490 Rugged Robotic Controller is a new embedded system. It is made for autonomous robots, edge AI, and industrial control. This rugged controller uses the Qualcomm® QCS6490 processor. It has an AI Engine, supports 5G and 4G, and has advanced GPU and ISP features. It provides real-time performance for AGVs, AMRs, machine vision, and mobile HMI deployments. This device has a fanless IP65 design. It features a PCAP touchscreen and works in a wide temperature range. It also has many I/O connections. This makes it great for tough industrial settings and smart edge computing.

## SPECIFICATIONS

### Display

Resolution	1920x1200	Size	10.1 inches
Contrast Ratio	800:1	Panel Brightness	800.0 nits
View Angles	85,85,85,85	Bonding	Optical Bonding for Sunlight Viewability
Type	Projected Capacitive Multi Touch	Viewability	AG+AF touch treatment

### System Specification

Processor	Qualcomm® 6490 (Octa-Core 2.7GHz)	Memory	8 GB
Storage	128GB	Operating System	Android 13.0
WLAN	Support	BT	Support
WWAN	4G LTE (Optional) 5G (Optional)	GNSS	GPS/GLONASS

### Mechanical

Dimension	317.75 x 188.87 x 35.8 mm	Cooling System	Fan Design
-----------	---------------------------	----------------	------------

### IO Ports

USB Port	1 x USB 3.0 (Type-A) 1 x USB 3.1 (Type C)	Video	2 x micro HDMI output
Audio	2x Speaker	LAN	1 x M8 LAN Connector (10/100 Mbps , Max to 250 Mbps)

### Environment

Operating Humidity	10% to 90% RH, non-condensing	Operating Temperature	-20°C to 60°C (AC mode), -10°C to 50°C (Battery mode)
Storage Temperature	-30°C to 70°C (-22°F to 158°F)	Shock	MIL-STD-810H Method 516.8 Procedure I
Vibration	MIL-STD-810H Method 514.8 Procedure I	IP rating	IP65

## Certification

Certification	CE, FCC
---------------	---------

## Control

Button	2 x Toggle Switch 2 x joystick 2 x Roller switch 6 x buttons
--------	---


## Power

Battery	10.9 V, typ. 6700 mAh Lilon Removable Battery (3S2P)	Power Rating	1 x USB (Type C) (Charging)
Adapter	PD Adapter 100W		

## Accessory

Accessory	1 x PD Adapter 100W 1 x M8 LAN external cable(2M) 1 x Power Cord	Optional Accessory	shoulder strap(Optional)
-----------	--	--------------------	--------------------------

## DIMENSIONS UNIT:MM



## NOTE

- 1.This is a simplified drawing and some components are not marked in detail.
- 2.Please contact our sales representative if you need further product information.
- 3.All specifications are subject to change without prior notice.
- 4.The product shown in this datasheet is a standard model.For diagrams that contain customized or optional I/ O, please contact the Winmate Sales Team for more information.